

KODAK PIXPRO AZ901

DIGITAL CAMERA



AZ901 ASTRO ZOOM

Introducing our most powerful Astro Zoom yet, the new KODAK PIXPRO AZ901 bridge camera offers a mind blowing 90X optical zoom and so much more. With a top-notch 20 megapixel BSI CMOS sensor, 5 fps multi-burst, 22mm wide angle lens and large 3" articulating LCD, photos and videos are crystal clear with amazing, razor sharp detail. Share your moments instantly with your friends and family via Wi-Fi® connectivity for even more flexibility. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 90X Optical Zoom
- 20 MP CMOS
- 5 fps Burst Shooting
- 3" Articulating LCD (920K Pixles)
- 360° Scan Panorama
- JPEG and RAW file format
- Wi-Fi Connection
- Wirelessly Control with your iOS™/ANDROID™ Device



Images are simulated.

Available Colors:

● BLACK



KODAK PIXPRO AZ901

DIGITAL CAMERA

SPECIFICATIONS	AZ901
Effective Image Sensor Pixels	20.68 Megapixels
Total Image Sensor Pixels	21.14 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length [35mm film equivalent]	3.9 mm (Wide) — 351 mm (Tele) [22 mm (Wide) — 1980 mm (Tele)]
F number	F3.1 (Wide) — F6.8 (Tele)
Lens Construction	14 groups 18 elements
Optical Zoom	90x
Focusing Range	Normal: (Wide) 50cm — ∞ (Tele) 500 — ∞ Macro: 5cm — ∞ (Wide Only)
Electronic Viewfinder	Yes (-3 ~ +1 diopter)
Anti-Handshake	Optical Image Stabilization
Digital Zoom	4x Digital Zoom (Combined Zoom: 360x)
Number of Recording Pixels	
Still Image	(4:3) 20MP: 5184x3888, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 18MP: 5184x3456, (16:9) 15MP: 5120x2880, 2MP: 1920x1080
Movie	1920x1080: 30fps, 1280x720: 60 fps / 30fps, 640x480: 30fps; High-Speed Movie 640x360: 120fps
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	JPEG (Best, Fine), RAW, RAW + JPEG (Best)
Movie	MOV [Image: H, 264; Audio: Linear PCM (Stereo)]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, WiFi, Movie, CS, SCN [ASCN, Panorama, Children, Portrait, Night Portrait, Handheld Night, Landscape, Sport, Sunset, Fireworks, Multi Exposure, Snow, Party, Pet]
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
Detection Features	Face, Smile, Blink, Cat, Dog
HDR	Yes
Scan Panorama	Up to 360°
LCD Display	3.0 inch (920K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Continuous AF, Object Tracking, Manual Focus
Focusing Area Selection	Single Area, 25-area, Face Detection, Manual
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available), Aperture Priority AE, Shutter Priority AE
Exposure Compensation	+/- 3EV in 1/3 Step Increments
Shutter Speed	1/2000 – 30 Seconds
Continuous Shooting	Approx. 5 fps (Full Resolution)
Playback Modes	Single, Index (9/16 Thumbnails) Slide Show, Date, Burst Shooting, Zoom (Approx. x2 – x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K ~ 10000K)
Flash	
Flash Method	Pop-up (Auto)
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Force Off, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.5m ~ 10.8m (ISO800) (Tele) Approx. 5.0m ~ 5.2m (ISO800)
Recording Media	SD/SDHC Card (Up to 32GB Support) [MMC Card not supported] Use Class 4 Card or Better
Other Features	Wi-Fi (802.11 b/g/n), Remote Control (via iOS/Android Device), Eye-Fi, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Power	Rechargeable Li-ion Battery LB-070, 7.4V 1020mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx.400 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 5.46 x 4.07 x 4.66 in. / 138.7 x 103.5 x 118.5 mm (Based on CIPA Standards)
Weight	Approx. 27.4 oz. / 777g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, USB Cable, Neck Strap, Lens Cap, CD-ROM, Service Card, Quick Start Guide, Warranty

JK Imaging Ltd.

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2018 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0038.0218.en.07

